to add the Latin-1 Supplement character set to the allowed ranges, which includes accented vowels and the German eszett character (ß).

Listing 3.10 Configuring the `WebEncoderOptions` to add the Latin-1 Supplement

```
builder.Services.Configure<WebEncoderOptions>(options =>
{
    options.TextEncoderSettings = new TextEncoderSettings(UnicodeRanges.BasicLatin,
UnicodeRanges.Latin1Supplement);
});
```

Note that whatever you set here will override the default settings, which is why you need to include the `BasicLatin` range. If you are unsure which character sets you should include, you can check here: http://www.unicode.org/charts/. Alternatively, you can simply specify `UnicodeRanges.All`.

TEMPLATED RAZOR DELEGATES

The *templated Razor delegate* feature enables you to use a delegate to create Razor templates and assign them to a variable for reuse. You may remember from our discussion on middleware in the previous chapter that a delegate is a type that represents a method signature and a return type. Razor template delegates are expressed as a `Func<dynamic, object>` (a generic delegate). The body of the method contains a snippet of Razor, with the opening HTML tag prefixed with an `@` symbol. The input parameter represents data and is a `dynamic` type, so it can represent anything. The data is accessible within the template through a parameter named `item`.

In listing 3.6, we created a list of cities and then rendered it to the browser using a `foreach` statement embedded in HTML to render an unordered list. In listing 3.11, we will extract the rendering of the unordered list into a template, which forms the body of the delegate.