Listing 3.17 A Razor layout page including a call to `RenderBody`

```
<!DOCTYPE html>
<html>
<head>
    <title></title>
    <link rel="stylesheet" href="~/lib/bootstrap/dist/css/bootstrap.min.css"
    ➥ />
</head>
<body>
    <div class="container">
        <header class="card alert-success border-5 p-3 mt-3">Header</header>
        <nav class="card alert-primary border-5 p-3 mt-2">Navigation</nav>
        <div class="row mt-2">
            <div class="col-3">
                <div class="card alert-warning p-5 border-5">
                    Deal Of The Day Widget 1
                </div>
            </div>
            <div class="col-9 card border-5">
                @RenderBody()                    ❶
            </div>
        </div>
        <footer class="card border-5 p-3 mt-2">Footer</footer>
    </div>
</body>
</html>
```

❶ This is the point at which the output from the content page is injected into the layout.

The `RenderBody` method call is the only requirement for a layout page. Everything else within the layout page is included in all content pages that reference it, which makes managing it very easy. Any changes you make to the layout are immediately applied to all pages that reference it.

3.2.1 Assigning the Layout property

The layout for a specific page is assigned programmatically via the page's `Layout` property. The value that you pass to the `Layout` property is a string, representing either the name of the layout file without its extension or the path to the layout file. Either of the approaches in the following listing will work.

Listing 3.18 Setting the layout page via the `Layout` property

```
@{
    Layout = "_Layout";
```