content is specified using the `@model` directive at the top of the partial file. For example, imagine that the data for your navigation menu is generated by the parent page and consists of a `Dictionary<string, string>`, where the keys represent the name of the page to link to, and the values represent the text for the link, perhaps. This is how the first line of the _NavigationPartial.cshtml file will look:

```
@model Dictionary<string,string>
```

The data itself will be generated by the page that references the partial and included in its own model as a property. You will see how this is done a bit later when you explore the `PageModel`. For the time being, you can assume that the data for this partial is represented by a property of the host page named `Nav`. You will pass this data to the partial tag helper's `model` attribute:

```
<partial name="_NavigationPartial" model="Model.Nav" />
```

Alternatively, you can use the `for` attribute to specify the data for the partial. This time, the `Model` is implicit:

```
<partial name="_NavigationPartial" for="Nav" />
```

You will see how you can also use partial views to generate HTML for use in partial page updates in AJAX scenarios in chapter 11.

3.3.2 Tag helpers

Tag helpers are components that automate the generation of HTML. They are designed to act on tags within the HTML of a Razor page. Many tag helpers are built into the ASP.NET Core framework, most of which target standard HTML tags, such as the anchor (you worked with one of these when you added the Welcome page to the navigation), input, link, form, and image tags. Others, like the partial tag helper you just saw, target custom tags you create yourself. Each tag