Guidance on building your own custom tag helper can be found in the official documentation (https://learn.microsoft.com/en-us/aspnet/core/mvc/views/tag-helpers/authoring?view=aspnetcore-7.0) or Andrew Lock's *ASP.NET Core In Action*, Second Edition (Manning, 2021).

The `addTagHelper` directive has a twin, `removeTagHelper`, that enables you to selectively opt certain tags out of processing. The following line of code opts out of anchor tag helper processing:

```
@removeTagHelper "Microsoft.AspNetCore.Mvc.TagHelpers.AnchorTagHelper,
➥ Microsoft.AspNetCore.Mvc.TagHelpers"
```

You can opt individual tags out of processing by placing the `!` prefix just prior to the tag name. For instance, you might want to do this if the specific element is only to be used by client-side code. Then there is no need to waste cycles having it processed on the server. The following example illustrates how that is applied to an anchor tag to prevent it from being processed unnecessarily:

```
<!a href="https://www.learnrazorpages.com">Learn Razor Pages</!a>
```

The prefix is placed in both the start and end tags. Any tag without the `!` prefix will be processed by an associated tag helper. The alternative is to opt specific tags *into* processing at parse time. You achieve this by registering a custom prefix with the `@tagHelperPrefix` directive and then applying your chosen prefix to tags you want to take part in the processing. You can register your prefix in the ViewImports file where you initially enabled tag helper processing:

```
@tagHelperPrefix x
```

You can use pretty much any string you like as a prefix. Then you apply it to both the start and end tags, just like the `!` prefix:

```
<xa asp-page="/Index">Home</xa>
```