Only those tags that feature the prefix will be processed. For the sake of clarity, most developers are likely to use punctuation to separate the prefix from the tag name—for example:

```
@tagHelperPrefix x:
<x:a asp-page="/Index">Home</x:a>
```

This should reduce any visual confusion, especially for designers when they look at the HTML content.

### *3.3.3 View components*

View components are a more advanced solution for generating reusable HTML. They are similar to partial views in that they can be used to help break up and simplify complex layouts, or they can represent part of a UI that can be used in multiple pages. View components are recommended instead of partial pages whenever any type of server-side logic is required to obtain or process data for inclusion in the resulting HTML snippet (specifically, calls to an external resource, such as a file, database, or web service). Typical scenarios in which view components work well include database-driven menus, tag clouds, and shopping carts—widgets that usually appear in a layout page and rely on their own source of data. View components also lend themselves to unit testing.

Since view components rely on advanced concepts that have not been covered so far, further discussion on the topic will have to wait if it is to make any sense. But rest assured, you will build a view component in chapter 14.

## *3.4 The PageModel*

You have now been introduced to the primary mechanisms for generating HTML within a Razor Pages application—the Razor page and the Razor syntax that enables dynamic content generation by mixing HTML with server-side C# code. You have also learned about some of the components that aid UI code reuse,