the type's `ToString()` method results in a suitable value for rendering. The following assignment adds a `DateTime` type to `ViewData`:

```
ViewData["SaleEnds"] = new DateTime(DateTime.Now.Year, 6, 30, 20, 0, 0);
```

If you want to render that value, you can do so simply:

```
<p>Sale ends at @ViewData[“SaleEnds”]</p>
```

The output is rendered according to the default settings of the server. In my case, that's English (United Kingdom), which results in `Sale Ends at: 30/06/2021 20:00:00` being rendered. If I want to use date and time formatting strings to control the rendering, I need to cast to a `DateTime`:

```
Sale Ends at: @(((DateTime)ViewData["SaleEnds"]).ToString("h tt, MMMM dd"))
```

Now I get the output I want: `Sale Ends at: 8 PM, June 30`.

You can set the value of `ViewData` items in the `PageModel` class. The next listing shows the title of the page being assigned to `ViewData` in a handler method called `OnGet`; you will learn about handler methods shortly.

**Listing 3.23 Assigning the `ViewData` value in `OnGet` in a `PageModel` class**

```
public class WelcomeModel : PageModel
{
    public void OnGet()
    {
        ViewData["Title"] = "Welcome!";
    }
}
```

For this assignment to take effect in the Razor page, you must ensure that the Razor page includes an `@model` directive referencing the `WelcomeModel` type:

```
@model WelcomeModel
```