```
    {
        Message = $"You searched for {searchTerm}";             ❸
    }

    public void OnPostRegister(string email)                    ❹
    {
        Message = $"You registered {email} for newsletters";    ❺
    }
}
```

❶ The Message property is added.

❷ The OnPostSearch method takes a string named searchTerm.

❸ The message incorporates the searchTerm parameter value.

❹ The OnPostRegister method processes a registration, with a parameter named email.

❺ The message incorporates the email parameter value.

Two handler methods are created: one is named `OnPostSearch`, and the other `OnPostRegister`. *Search* and *Register* represent the *name* part of the named handler methods. Both methods take a string parameter, but they each set the `Message` property to a different value based on which method was invoked.

Listing 3.32 shows two simple forms in the Index page—one for searching and the other for registering. The form tag is one of those that a tag helper targets, so custom attributes are made available. The `page-handler` attribute accepts the name of a page handler method to be used to process the request when the form is submitted.

Listing 3.32 The `page-handler` attribute enables targeting of different handler methods

```
@page
@model WelcomeModel
@{
}

<div class="col">
    <form method="post" asp-page-handler="Search">      ❶
        <p>Search</p>
        <input name="searchTerm" />                     ❷
        <button>Search</button>
    </form>

    <form method="post" asp-page-handler="Register">
        <p>Register</p>
```