It is possible to configure an alternative root for Razor pages through the `RazorPagesOptions` object during the bootstrapping phase. The following example changes the root directory to Content instead of Pages:

```
builder.Services.AddRazorPages().AddRazorPagesOptions(options => {
    options.RootDirectory = "/Content";
});
```

Or you can use the `WithRazorPagesRoot` extension method:

```
builder.Services.AddRazorPages().WithRazorPagesRoot("/Content");
```

For a Razor file to be seen as a navigable page, it needs to have an `@page` directive at the top, and it cannot have a leading underscore in its name. Table 4.2 shows the route templates generated for the default project template pages along with the URL that matches the generated template.

Table 4.2 Route templates are constructed from the filename and location

Page	Route template	Matches
\Pages\Index.cshtml	`"Index"`	https://domain.com/index
\Pages\Index.cshtml	`""`	https://domain.com/
\Pages\Privacy.cshtml	`"Privacy"`	https://domain.com/privacy
\Pages\Error.cshtml	`"Error"`	https://domain.com/error

The Index.cshtml file is a special case. Two route templates are generated for it—one that includes the filename and another consisting of an empty string instead of Index. This happens because Index is seen as the default document. Therefore, it can be reached just by matching the folder name in the URL. If you are not careful, this can cause problems resulting from ambiguous routes. For example, if you add a folder named Privacy with an Index file in it, the route templates in table 4.3 will be generated.