property, which is the recommended way to work with route data, rather than accessing the route values dictionary. Listing 4.3 shows the `CityModel OnGet` method amended to take a parameter called `cityName` and assigning the incoming value to a public property, followed by the change in the City Razor page to work with it.

Listing 4.3 Binding route data to `PageModel` handler parameters

```
[City.cshtml.cs]
public class CityModel : PageModel
{
    public string CityName { get; set; }     ❶
    public void OnGet(string cityName)       ❷
    {
        CityName = cityName;                 ❸
    }
}


[City.cshtml]
@page "{cityName=Paris}"
@model CityBreaks.Pages.CityModel
@{
}
<h3>@Model.CityName Details</h3>             ❹
```

❶ A public property is added to the PageModel.

❷ A parameter is added to the OnGet, which is named the same as the route parameter and is the same data type.

❸ The parameter value is assigned to the PageModel property.

❹ The PageModel property is referenced in the page instead of RouteData.Values.

You can specify multiple parameters in a route template. Often, each parameter will occupy its own segment in a URL. Listing 4.4 shows the City page and its `PageModel` updated to handle an additional optional parameter in a new URL segment that might enable the user to specify the minimum acceptable rating of potential venues within the specified city.

Listing 4.4 Multiple parameters in separate URL segments