Constraint	Description	Example
`alpha`	Matches uppercase or lowercase Latin alphabet characters (a-z or A-Z)	`{title:alpha}`
`bool`	Matches a Boolean value	`{isActive:bool}`
`int`	Matches a 32-bit integer value	`{id:int}`
`datetime`	Matches a `DateTime` value	`{startdate:datetime}`
`decimal`	Matches a decimal value	`{cost:decimal}`
`double`	Matches a 64-bit floating-point value	`{latitude:double}`
`float`	Matches a 32-bit floating-point value	`{x:float}`
`long`	Matches a 64-bit integer value	`{x:long}`
`guid`	Matches a GUID value	`{id:guid}`
`length`	Matches a string with the specified length or within a specified range of lengths	`{key:length(8)}` `{postcode:length(6,8)}`
`min`	Matches an integer with a minimum value	`{age:min(18)}`
`max`	Matches an integer with a maximum value	`{height:max(10)}`
`minlength`	Matches a string with a minimum length	`{title:minlength(2)}`
`maxlength`	Matches a string with a maximum length	`{postcode:maxlength(8)}`
`range`	Matches an integer within a range of values	`{month:range(1,12)}`
`regex`	Matches a regular expression	`{postcode:regex(^[A-Z]{2}\d\s?\d[A-Z]{2}$)}`

Earlier in the chapter, you saw how ambiguous routes were created when an Index file was added to a Privacy folder. The same situation will arise if you