add a City folder and place an Index file there. Last time, I provided an entirely new route template to one of the pages to prevent duplicate route templates being generated. Constraints can also be used to ensure each page is seen as different. A template of `"{cityName:alpha}"` requires parameters to consist only of letters (a-z or A-Z), while a template `"{id:int}"` will only match numbers.

It is possible to apply multiple constraints to a parameter. For example, you might want to specify that a value must be composed only of letters of the alphabet and must not exceed nine characters in length. This is achieved by appending additional constraints using the colon separator:

```
"{cityName:alpha:maxlength(9)}"
```

CUSTOM ROUTE CONSTRAINTS

As table 4.5 demonstrates, an extensive range of route constraints that should meet most of your needs is available to you. It is also possible to create your own custom route constraint and register that with the routing service for application-specific needs.

Eventually, your City page is likely to take the value passed in to the `cityName` parameter and use that to perform a lookup against a database to obtain more details for the specified location. This works fine, but you soon begin to realize that sometimes the database query doesn’t return a result. When you review your logs, you see that the value being passed to the database query is not what you expect to see in your URLs. It might be part of a city name, it might have some extra characters added, or, indeed, it might bear no resemblance to anything in your database at all. There are countless ways links to your site can get broken when shared or stored by a