NOTE The process of providing support for content to be displayed in multiple languages is known as *localization*, which is a specialized topic and won't be covered in any detail in this book beyond this example. If you would like to know more about localization in Razor Pages, check out my series of blog articles here: https://www.mikesdotnetting.com/category/41/localization.

To present a localized (translated) version of the content, the application needs to know which *culture*, or language, the user prefers. Often, this is determined by asking the user to select from a number of options and then tracking that selection in some way. One of the common ways to store the selection and pass it from page to page is in the URL as data. A typical example of a URL that includes the preferred culture might be https://domain.com/en/Welcome, where the /en/ segment specifies English as the culture, or https://domain.com/fr/Welcome for the French version.

As already established, you pass data in URLs as parameter values, and route templates that incorporate parameters need to be declared explicitly. If you want to support adding a route template to multiple pages, you can create a `PageRoute- ModelConvention` that can be applied to any number of pages.

`PageRouteModelConventions` implement the `IPageRouteModelConvention` interface, which specifies a single method that must be implemented—the `Apply` method, which takes a `PageRouteModel` as a parameter:

```
public interface IPageRouteModelConvention : IPageConvention
{
    void Apply(PageRouteModel model);
}
```

Notice that the `IPageRouteModelConvention` interface, in turn, implements the `IPageConvention` interface. This is a *marker interface*. It has no methods and is used as part of the route discovery