You can change this behavior so that the name of the handler becomes part of the URL by altering the page's route template to include a parameter named `"handler"`. This is usually added as an optional parameter, so the regular `OnGet` and `OnPost` handlers can also be reached:

```
@page "{handler?}"
```

The `route-*` attribute caters to route parameter values, where the `*` represents the name of the parameter. Following is a tag helper that generates a link to the city page for Rome using the `cityName` parameter you specified in the route template:

```
<a asp-page="/City" asp-route-cityName="Rome">Rome</a>
```

If the parameter is not part of the route template, the name and value passed to the `route-*` attribute is applied to the URL query string. So if you replace the `route` attribute in the previous example with `asp-route-foo="bah"`, the resulting URL will be `/City?foo=bah`.

The `all-route-data` parameter takes a `Dictionary<string, string>` as a value, which is used to wrap multiple route parameter values. It is provided as a convenience that relieves you from having to add multiple `route-*` attributes:

```
var d = new Dictionary<string, string> { { "cityName", "Madrid" },{ "rating",
➥ "5" } };
<a asp-page="/City" asp-all-route-data="d">Click</a>
```

The default behavior of the anchor tag helper is to generate a relative URL based on the location of the target page. Suppose you choose to specify the protocol (e.g., HTTPS) using the `protocol` attribute or the hostname