in the `Program` class, like the `CultureTemplatePageRouteModelConvention` from earlier in the chapter:

```
builder.Services.AddRazorPages().AddRazorPagesOptions(options => {
    options.Conventions.AddPageRoute("/Index", "FindMe");
    options.Conventions.Add(new CultureTemplatePageRouteModelConvention());
    options.Conventions.Add(new PageRouteTransformerConvention(
        new KebabPageRouteParameterTransformer()));
});
```

The `PageRouteTransformerConvention` type implements the `IPageRouteModelConvention` interface. You were introduced to that interface and its `Apply` method earlier as part of the `CultureTemplatePageRouteModelConvention`. When the application starts up, your new parameter transformer is assigned to the `PageRouteModel`'s `RouteParameterTransformer` property within the `Apply` method of the `PageRouteTransformerConvention`. From there, its logic is applied whenever an outbound route is required.

TRANSFORMING ROUTE PARAMETER VALUES

The final part of our look at managing URLs generation focuses on customizing route parameter values. Imagine you have a list of cities, and you want to generate links for each one as the route parameter value for the City page. Putting into practice what you have learned over the last couple of chapters, you might come up with some code that looks like the following listing in your `PageModel` class.

Listing 4.14 Generating an array of cities in the `PageModel`