their form control names, as key-value pairs to the `Request.Form` collection. In ASP.NET Core, each item can be accessed using a string-based index (e.g., `Request.Form["password"]`), where the value of the index is the name of the original form control. The return type is a `StringValues` object, which differs from previous versions of ASP.NET, where the return type was a simple string.

To see this in action, you will create a very simple form that enables a user to type the name of a city into a form, and then submit that information to the server for processing. Your server-side code will extract the name of the submitted city from the HTTP request and display it back to the user.

First, create a new folder in the Pages folder, and name it CityManager. Then add a new Razor page named Create.cshtml to the CityManager folder. Replace the code in Create.cshtml with the following.

Listing 5.1 The Create page with a form

```
@page
@model CityBreaks.Pages.CityManager.CreateModel
@{
   ViewData["Title"] = "Create City";
}
<div class="col-4">
    <form method="post">                                                    ❶
        <div class="mb-3">
            <label for="name">Enter city name</label>
            <input class="form-control" type="text" name="cityName" />      ❷
        </div>
        <button class="btn btn-primary">Submit</button>
    </form>
    <p>@Model.Message</p>                                                   ❸
</div>
```

❶ The form method is set to post.

❷ The name attribute of the text input is set to "cityName".

❸ A PageModel property called Message is rendered here.