This is standard HTML for a form that is styled with Bootstrap classes. It includes an input with the `name` attribute set to `"cityName"`. The `name` attribute is the most important one on any form control because this is used as the key of the key-value pairs sent to the server when the form is submitted. This often surprises ASP.NET Web Forms developers, who are conditioned to see the `id` property of a server control as the means for identifying the source of incoming form values and tend to confuse this with the `id` attribute on an HTML element.

The incoming collection of key-value pairs is assigned to the `Form` property of the `Request` object. Both the `PageModel` class and the Razor page provide direct access to the `Request` object via a property conveniently named `Request`, which bypasses the need to access it via the `HttpContext` property. The next step is to change the `PageModel` class file content, so it looks like the content of the following listing.

Listing 5.2 Processing the form values using `Request.Form`

```
using Microsoft.AspNetCore.Mvc.RazorPages;
using Microsoft.Extensions.Primitives;                                    ❶

namespace CityBreaks.Pages.CityManager
{
    public class CreateModel : PageModel
    {
        public string Message { get; set; }                               ❷
        public void OnPost()                                              ❸
        {
            if(!StringValues.IsNullOrEmpty(Request.Form["cityName"]))     ❹
            {
                Message = $"You submitted {Request.Form["cityName"]}";    ❺
            }
        }
    }
}
```