HTML provides two options for making multiple selections: a `select` element with the `multiple` attribute applied to it (aka a *list box* control) and a series of inputs with their `type` attribute set to `checkbox.` They must all share exactly the same name attribute; you can use whichever you prefer. The choice between them depends on your UI preference.

The next code example features a form where the user can select more than one option using check boxes. In this case, the user is invited to select from a number of cities. The selection will be bound to a `List<int>`, where each element represents one of the values that was selected. You need to add another class to the Models folder that will represent a city and have two properties.

Listing 5.13 The `City` class

```
public class City
{
    public int Id { get; set; }
    public string Name { get; set; }
}
```

Next, change the `CityModel` in City.cshtml.cs to include a `List` of `int` as a binding target and some code to generate a `List` of cities.

Listing 5.14 The `CityModel` class

```
public class CityModel : PageModel
{
    [BindProperty]                                                          ❶
    public List<int> SelectedCities { get; set; } = new List<int>();        ❶
    public List<City> Cities = new List<City>                               ❷
    {
        new City{ Id = 1, Name = "London"},
        new City{ Id = 2, Name = "Paris" },
        new City{ Id = 3, Name = "New York" },
        new City{ Id = 4, Name = "Rome" },
        new City{ Id = 5, Name = "Dublin" }
```