```
<h4>Create Countries</h4>

<div class="row">
    <div class="col-md-8">
        <form method="post">
            <table class="table table-borderless">
               <tr>
                    <th>Name</th>
                    <th>ISO-3166-1 Code</th>
               </tr>
            @for (var i = 0; i < 5; i++)
            {
               <tr>
                    <td class="w-75">
                    <input name="Inputs[@i].CountryName"    ❶
                    ➥ class="form-control" />              ❶
               </td>
                    <td class="w-25">
                    <input name="Inputs[@i].CountryCode"    ❶
                    ➥ class="form-control" />              ❶
               </td>
               </tr>
            }
            </table>
            <div class="form-group">
               <input type="submit" value="Create" class="btn btn-primary" />
            </div>
        </form>
    </div>
</div>
@if (Model.Countries.Any())
{
    <p>You submitted the following</p>
    <ul>
    @foreach (var country in Model.Countries)
    {
        <li>
            <img src="/images/flags/@(country.CountryCode).png" />
            @country.CountryName
        </li>
    }
    </ul>
}
```

❶ Increment the variable `i` by 1 on each iteration, and use its value to generate the index value on the form controls.

When the form is submitted, a collection of five `InputModel` objects is instantiated by the model binder and populated with the posted values. If the