Table 5.2 Validation attributes for use in Razor Pages

Attribute	Description
`Compare`	Used to specify another property that the value should be compared to for equality. `[Compare(nameof(Password2))]`
`MaxLength`	Sets the maximum number of characters/bytes/items that can be accepted. `[MaxLength(20)]`
`MinLength`	Sets the minimum number of characters/bytes/items that can be accepted. `[MinLength(2)]`
`PageRemote`	Enables client-side validation against a server-side resource, such as a database check to see if a username is already in use.

`Range`	Sets the minimum and maximum values of a range.
	`[Range(5,8)],`
	`Range(typeof(DateTime),"2021-1-1","2021-12-31")]`

`RegularExpression`	Checks the value against the specified regular expression. `[RegularExpression(@"[a-zA-Z]+")]`
`Required`	Specifies that a value must be provided for this property. Non-nullable value types, such as `DateTime` and numeric values, are treated as required by default and do not need this attribute applied to them. `[Required]`
`StringLength`	Sets the maximum and, optionally, the minimum number of string characters allowed. `[StringLength(2)], [StringLength(10, MinimumLength=2)]`

In addition, there are some data type validation attributes, including `Phone`, `EmailAddress`, `Url`, and `CreditCard`. These validate incoming values against predetermined formats to ensure that they are “well formed.” Documentation on what the attribute authors consider to be well formed is sparse, but you can always resort to looking at the source code to