see the logic used to test the incoming value to ensure the implementation covers your business rules. The .NET Source Browser is a great tool for this purpose (https://source.dot.net/). Using that, or going directly to the source code for the `EmailAddressAttribute` (http://mng.bz/44ww), for example, will show you that the "validation" consists of little more than checking the presence of the `@` character in the input. The check ensures there is only one instance of the character, and it is not at the beginning or end of the input. So `a@b` will pass this validation.

Aside from the `PageRemote` attribute, all the other attributes cause validation to occur on both the client and the server. The `PageRemote` attribute uses client-side code to validate against the server. See http://mng.bz/QvBG for more details on usage.

Attributes are applied to `PageModel` properties or properties of an input model. They can also be applied to handler method parameters, but you lose out on automatic client-side validation if you bind to handler parameters rather than `PageModel` properties. We will only look at applying validation attributes to properties. Server-side validation is enabled by default. Client-side validation must be specifically enabled.

5.3.2 Client-side validation

Client-side validation should only ever be viewed as a courtesy to users, in that it provides immediate feedback to the user in the event that they have not provided satisfactory input. Your application must not rely solely on client-side validation because it is very easy to circumvent by anyone who has a small amount of HTML or JavaScript knowledge. Client-side validation support is currently provided by the jQuery Unobtrusive