Listing 5.23 Using validation tag helpers to emit validation error messages

```
<form method""pos"">
    <div class""form-grou"">
        <label for""Input.CountryNam"" class""control-labe"">Name</label>
        <input asp-for""Input.CountryNam"" class="form-control" />          ❶
        <span asp-validation-for="Input.CountryName"                       ❶
        ➥ class="text-danger"></span>                                     ❶
    </div>
    <div class="form-group">
        <label for="Input.CountryCode" class="control-label">ISO-3166-1
        ➥ Code</label>
        <input asp-for="Input.CountryCode" class="form-control" />         ❶
        <span asp-validation-for="Input.CountryCode"                       ❶
        ➥ class="text-danger"></span>                                     ❶
    </div>
    <div class="form-group">
        <input type="submit" value="Create" class="btn btn-primary" />
    </div>
</form>
```

❶ Input tag helpers and validation tag helpers are added to the form for both properties.

In addition, to activate client-side validation, you must reference the validation scripts, so add the following to the bottom of the Razor page.

Listing 5.24 Adding `ValidationScriptsPartial` for client-side validation

```
@section scripts{
    <partial name="_ValidationScriptsPartial"/>
}
```

Run the application, and navigate to /country-manager/create. If you try to submit the form without entering any data, you will see error messages. If you try to submit a single character in the `CountryCode` input, a different error message will appear. Notice that you cannot enter more than two characters into that control. Take a look at the HTML that was generated for the `CountryCode` input.