Listing 5.25 The rendered HTML for the `CountryCode` property input

```
<input
    class="form-control"
    type="text"
    data-val="true"
    data-val-length="The field CountryCode must be a string     ❶
    ➥ with a minimum length of 2 and a maximum length of 2."  ❶
    data-val-length-max="2"                                    ❶
    data-val-length-min="2"                                    ❶
    data-val-required="The CountryCode field                   ❷
    ➥ is required."                                           ❷
    id="Input_CountryCode"
    maxlength="2"                                              ❶
    name="Input.CountryCode"
    value=""
/>
```

❶ These attributes were generated because the StringLength attribute was applied to the property.

❷ This is the default error message generated by the inclusion of the Required attribute.

I've broken it over multiple lines for readability, but you can see a number of `data-val` attributes have been added to the rendered input. These attributes relate to the various types of validation you want to subject the value to. They include the default error messages that will be displayed along with the parameters that valid values must fall within. Following is the content of the span tag helper generated by the client-side validation library when the user attempts to submit a value that is less than the `data-val-length-min` value.

Listing 5.26 The generated source for the validation tag helper when an error occurs

```
<span class="text-danger field-validation-error"
    data-valmsg-for="Input.CountryCode"
    data-valmsg-replace="true">
    <span id="Input_CountryCode-error" class="">
        The field CountryCode must be a string with a minimum length
            of 2 and a maximum length of 2.
    </span>
</span>
```