❷ Check ModelState.

❸ If all is OK, assign the form values to the TempData properties and redirect to another page.

❹ Or redisplay the form.

You have introduced a new item here: `TempData`. This is another dictionary that is designed to hold values for the duration of the next request. Its most common use is to retain state during a redirect, such as is used in this example. If you apply the `TempData` attribute to a simple property (e.g., a string), it is automatically added to the dictionary.

The `OnPost` handler has been altered to test `ModelState.IsValid`. If it is valid, the incoming values are assigned to the string properties, and the user is redirected to a page called Success. If not, the user is shown the form again. So you need a new page named Success.cshtml. This should be added to the CountryManager folder, and the Razor page should be altered to look like the following listing.

Listing 5.29 The Success page content

```
@page
@model CityBreaks.Pages.CountryManager.SuccessModel
<h1>Success!</h1>
<p>Your form submission was completed. You submitted:</p>
<p>
     @TempData["CountryName"]
    <img src="/images/flags/@(TempData["CountryCode"]).png" />
</p>
```

Run the application, and navigate to country-manager/create. If you try to submit an invalid form, you will see the error messages, as previously. The difference is that these error messages were generated by the server, not the browser. Despite that, any values you entered into the form are retained, which are repopulated from the `ModelState` dictionary. When you submit valid values, you are redirected to the Success page, and details of your submission are shown (figure 5.12).