In this example, the label tag helper is empty. It has no content. When used like this, the property name is rendered within the label:

```
<label for="CityName">CityName</label>
```

You can override this by adding your text to the label's content or by using a data annotation attribute, which we will look at shortly.

So to summarize, the benefit of using tag helpers in forms is that you establish a two-way binding relationship between the property in your server code and the form control rendered to the browser. If the value is updated in the form, that update is applied automatically on the server when submitted. Equally, if you change the value on the server, the rendered form control will reflect those changes automatically.

## *6.2.1 Understanding the input types*

Now that you understand the benefits of using tag helpers in forms, it's time to look at ways to ensure the correct type of input is rendered. First, we will look at the default mapping between .NET and HTML types. HTML 5 added support for a collection of new input types for different kinds of data—`number`, `datetime-local`, `week`, and `range`—on top of the existing options that include `checkbox`, `radio`, `file,` and so on. Some of the HTML 5 input types only enjoy limited support across browsers, but where you can, you should make use of them before reaching for third-party libraries (e.g., date pickers) that provide similar features.

You can often rely on Razor Pages generating the correct type based purely on the property's data type that is bound to the tag helper. Table 6.1 provides details on which value is generated for the HTML `type` attribute by the input tag helper for the specified .NET data types.