## Listing 6.3 The form for the Create Property page, using tag helpers

```
@page
@model CityBreaks.Pages.PropertyManager.CreateModel
@{
    ViewData["Title"] = "Create Property";
}

<form method="post">
    <div class="mb-3">
        <label class="form-label" asp-for="Name"></label>
        <input class="form-control" asp-for="Name" />
    </div>
    <div class="mb-3">
        <label class="form-label" asp-for="MaxNumberOfGuests"></label>
        <input class="form-control" asp-for="MaxNumberOfGuests" />
    </div>
    <div class="mb-3">
        <label class="form-label" asp-for="DayRate"></label>
        <input class="form-control" asp-for="DayRate" />
    </div>
    <div class="mb-3">
        <label class="form-label" asp-for="AvailableFrom"></label>
        <input class="form-control" asp-for="AvailableFrom" />
    </div>
    <div class="mb-3">
        <label asp-for="SmokingPermitted"></label>
        <input asp-for="SmokingPermitted" />
    </div>
    <div class="mb-3">
        <button class="btn btn-primary">Submit</button>
    </div>
</form>
```

Aside from the Bootstrap classes used for presentation, the form consists of a series of label and input tag helpers representing each property in the `PageModel`. When you navigate to /property-manager/create, you should see something similar to figure 6.2.