Figure 6.2 The rendered form for the Create Property page

The label tag helpers have rendered the name of the property, and this value has also been assigned to the rendered label's `for` attribute. Some of these label values are not particularly user friendly. We'll look at ways you can manage that a bit later.

The inputs have been generated according to the data type of the associated property, as described in the table 6.1. Notice that several inputs already have a value assigned even though you haven't set one. The associated properties are not nullable, so they are considered to be required, and their default value has already been assigned to them. Now let's take a look at the rendered source code for the form.

Listing 6.4 The rendered source for the form

```
<form method="post">
    <div class="mb-3">
        <label class="form-label" for="Name">Name</label>
        <input class="form-control" type="text" id="Name"
         ➥ name="Name" value="" />
    </div>
    <div class="mb-3">
        <label class="form-label"
         ➥ for="MaxNumberOfGuests">MaxNumberOfGuests</label>
        <input class="form-control" type="number" data-val="true"
data-val-required="The MaxNumberOfGuests field is required."
id="MaxNumberOfGuests" name="MaxNumberOfGuests" value="0" />
    </div>
    <div class="mb-3">
        <label class="form-label" for="DayRate">DayRate</label>
        <input class="form-control" type="text" data-val="true"
data-val-number="The field DayRate must be a number."
➥ data-val-required="The DayRate field is required."
➥ id="DayRate" name="DayRate" value="0.00" />
    </div>
    <div class="mb-3">
        <label class="form-label" for="AvailableFrom">AvailableFrom</label>
        <input class="form-control" type="datetime-local" data-val="true"
        ➥ data-val-required="The AvailableFrom field is required."
        ➥ id="AvailableFrom"
 name="AvailableFrom" value="0001-01-01T00:00:00.000" />
```