```
    </div>
    <div class="mb-3">
        <label for="SmokingPermitted">SmokingPermitted</label>
        <input type="checkbox" data-val="true"
        ➥ data-val-required="The SmokingPermitted field is required."
        ➥ id="SmokingPermitted" name="SmokingPermitted" value="true" />
    </div>
    <div class="mb-3">
        <button class="btn btn-primary">Submit</button>
    </div>
<input name="__RequestVerificationToken" type="hidden" value="CfDJ...F4" />
<input name="SmokingPermitted" type="hidden" value="false" />
</form>
```

All of the non-nullable properties include the additional client-side validation attributes you met in the last chapter: `data-val` and `data-val-required`. The `data-val` attribute is set to `true` for each property. The `data-val-required` attribute has an error message assigned to it customized to the associated property.

Ignoring the request verification token, which I cover in chapter 13, one other point of interest is that two inputs have been generated for the `SmokingPermitted` property. The first is the check box you would expect to see rendered for a Boolean value, based on the mapping described in table 6.1. The second is a hidden input included just before the closing form tag:

```
<input name="SmokingPermitted" type="hidden" value="false" />
```

Normally, no value is passed to the server for the associated property when the form is submitted if a check box is not checked. The hidden field will ensure that a name-value pair will be included in the form submission, regardless of whether the check box is checked or not. If the check box is checked, the posted value will be `true,false`. Otherwise, it will be `false`. Based on this, the model binder will be able to infer the correct value to assign to the `PageModel` property. This behavior is really a