The week input type is used to select a week of the year, based on the ISO 8601 week number. The format supported by the week input is `yyyy-Www`, where `-W` is literal and `ww` represents the week of the year. The default model binder doesn't include support for this format because .NET doesn't support this as a valid date/time format string. If you need to work with the week input type, you must generate a value in the correct format yourself. Then you can either parse the value from `Request.Form` yourself, or you can implement your custom model binder. That is an advanced topic that won't be covered in this book, but you can refer to my blog post that provides an example specific to working with the week input type: http://mng.bz/M5eW.

6.2.4 Using the DisplayAttribute to control labels

Earlier, I noted that many of the rendered label values in the form (figure 6.1) lacked user friendliness. The label tag helper simply took the name of the C# property and rendered it as is—Pascal casing included. This is what happens if you leave the content of the label tag helper empty, as we did in this example form. One way to override this behavior is providing your content within each instance of the label tag:

```
<label asp-for="DayRate">Day Rate</label>
```

Alternatively, you can apply the `DisplayAttribute` to the property to control the output by assigning your preferred label text to its `Name` property:

```
[BindProperty]
[Display(Name="Day Rate")]
public decimal DayRate { get; set; }
```

The primary benefit of this approach is that you centralize the configuration, so you don't have to hunt around in the Razor page to make changes. The following listing shows the revised `PageModel` properties for the Create Property page with data type and display attributes applied. Figure 6.5