of a `SelectList`. To see how this works, you will add a new element to the property creation form that enables the user to specify the city where the property is located. Adjust the `CreateModel` class in the PropertyManager folder to include the two additional highlighted properties, ensuring the `SelectedCity` property is decorated with the `BindProperty` attribute.

Listing 6.7 Adding properties to represent options and the selected value

```
public class CreateModel : PageModel
{
    [BindProperty]
    public string Name { get; set; }
    [BindProperty]
    public int MaxNumberOfGuests { get; set; }
    [BindProperty]
    public decimal DayRate { get; set; }
    [BindProperty]
    public bool SmokingPermitted { get; set; }
    [BindProperty]
    public DateTime AvailableFrom { get; set; }
    [BindProperty]                                          ❶
    [Display(Name="City")]                                  ❶
    public string SelectedCity { get; set; }                ❶
    public SelectList Cities { get; set; }                  ❷

    public void OnGet()                                     ❸
    {                                                       ❸
        var cities = new[] { "London", "Berlin", "Paris",   ❸
                             ➥ "Rome", "New York" };       ❸
        Cities = new SelectList(cities);                    ❸
    }                                                       ❸
}
```

❶ The SelectedCity property represents the selected value.

❷ The Cities property represents the options that the user can select from.

❸ An OnGet handler containing code that creates an array of city names and passes to the SelectList constructor is added.