```
    }
}
```

❶ Inject the IWebHostEnvironment service into the CreateModel, so you can use it to locate the wwwroot folder.

❷ Add binding targets for the city name and image upload.

❸ Add a TempData property to represent the image filename.

❹ Assign the submitted city name to TempData.

❺ Rename the uploaded file, and save it to a folder named cities in the image folder.

❻ Redirect the user.

The `IWebHostEnvironment` service provides information about the web hosting environment an application is running in. You inject it into the `CreateModel` to use its `WebRootPath` property to locate the wwwroot folder, then you add binding targets for the city name and the file upload. Both are made mandatory—being decorated with the `Required` attribute—and the `Upload` property is also decorated with your new validation attribute. You have chosen only to accept JPG files. You have also added another property that is decorated with the `TempData` attribute. You will use this to store the filename of the uploaded image, so it is available when you redirect the user.

If validation succeeds, you will take the submitted city name and add it to `TempData`:

```
TempData["Name"] = Name;
```

But why didn't you just add a `TempData` attribute to the existing `Name` property, as you did with the `Photo` property? Well, the `TempData` attribute enables you to both set *and* get values from `TempData`. Model binding and `TempData` conflict with each other because they both provide a mechanism to populate page properties with values from an HTTP request.