You will use the Fluent API `HasData` method to specify seed data for an entity as part of its configuration. You must specify primary and foreign key values, so the migration can determine if any changes have been made to data outside of migrations. Such changes will be overwritten, so the seeding feature is most suitable for static data that will not change. If data is likely to change once it has been added using the seeding feature, you can comment out the relevant code, so it is not called in subsequent migrations. The following listing shows the `Configure` method in the `CountryConfiguration` class amended to include the `HasData` method call, which takes a collection of the relevant types.

**Listing 8.10 `Country` seed data**

```
public void Configure(EntityTypeBuilder<Country> builder)
{
    builder.Property(x => x.CountryName)
        .HasMaxLength(50);
    builder.Property(x => x.CountryCode)
        .HasColumnName("ISO 3166 code")
        .HasMaxLength(2);
    builder.HasData(new List<Country>
    {
        new Country {Id = 1, CountryName = "Croatia", CountryCode="hr" },
        new Country {Id = 2, CountryName = "Denmark", CountryCode =  "dk" },
        new Country {Id = 3, CountryName = "France", CountryCode = "fr" },
        new Country {Id = 4, CountryName = "Germany", CountryCode = "de" },
        new Country {Id = 5, CountryName = "Holland", CountryCode = "nl" },
        new Country {Id = 6, CountryName = "Italy", CountryCode = "it" },
        new Country {Id = 7, CountryName = "Spain", CountryCode = "es" },
        new Country {Id = 8, CountryName = "United Kingdom",
        ➥ CountryCode = "gb" },
        new Country {Id = 9, CountryName = "United States",
        ➥ CountryCode = "us" }
    });
}
```

To add seed data for cities, you first need to add a property to the `City` class to represent an image. I will call this property `Photo`, but you will configure it to map to a column named `Image`.