Listing 8.11 Adding the `Photo` property to the `City` class

```
public class City
{
    public int Id { get; set; }
    public string Name { get; set; }
    public string Photo { get; set; }
    public int CountryId { get; set; }
    public Country Country { get; set; }
    public List<Property> Properties {  get; set; } = new List<Property>();
}
```

Now you need to add another `IEntityTypeConfiguration` class to the Configuration folder, this time named `CityConfiguration`, with the following code.

Listing 8.12 The `City` configuration class

```
using CityBreaks.Models;
using Microsoft.EntityFrameworkCore;
using Microsoft.EntityFrameworkCore.Metadata.Builders;

namespace CityBreaks.Data.Configuration;
public class CityConfiguration : IEntityTypeConfiguration<City>
{
    public void Configure(EntityTypeBuilder<City> builder)
    {
        builder.Property(x => x.Photo).HasColumnName("Image");
        builder.HasData(new List<City>
        {
            new City { Id = 1, Name = "Amsterdam", CountryId = 5,
            ➥ Photo = "amsterdam.jpg" },
            new City { Id = 2, Name = "Barcelona", CountryId = 7,
            ➥ Photo ="barcelona.jpg" },
            new City { Id = 3, Name = "Berlin", CountryId = 4,
            ➥ Photo ="berlin.jpg" },
            new City { Id = 4, Name = "Copenhagen", CountryId = 2,
            ➥ Photo ="copenhagen.jpg" },
            new City { Id = 5, Name = "Dubrovnik", CountryId = 1,
            ➥ Photo ="dubrovnik.jpg" },
            new City { Id = 6, Name = "Edinburgh", CountryId = 8,
            ➥ Photo ="edinburgh.jpg" },
            new City { Id = 7, Name = "London", CountryId = 8,
            ➥ Photo ="london.jpg" },
            new City { Id = 8, Name = "Madrid", CountryId = 7,
            ➥ Photo ="madrid.jpg" },
```