```
            new City { Id = 9, Name = "New York", CountryId = 9,
            ➥ Photo ="new-york.jpg" },
            new City { Id = 10, Name = "Paris", CountryId = 3,
            ➥ Photo ="paris.jpg" },
            new City { Id = 11, Name = "Rome", CountryId = 6,
            ➥ Photo ="rome.jpg" },
            new City { Id = 12, Name = "Venice", CountryId = 6,
            ➥ Photo ="venice.jpg" }
        });
    }
}
```

Note that you have used the `HasColumnName` method to map the `Photo` property to a column named `Image`.

The final configuration is for the `Property` type. This configuration consists purely of seed data, and the example in the book's downloads includes 50 fictitious property details. You can either generate your seed data based on what you have learned so far or copy the configuration file's contents from the book's GitHub repo: http://mng.bz/yaBd.

Once the configuration classes are done, you will need to register them with the `DbContext`. You can do this by overriding the `OnModelCreating` method in the `CityBreaksContext` class and then using the `ModelBuilder ApplyConfiguration` method to register each type. Since the `ApplyConfiguration` method returns a `ModelBuilder`, you can chain these calls.

Listing 8.13 Registering configurations in the `OnModelCreating` method

```
protected override void OnModelCreating (ModelBuilder builder)
{
    builder
        .ApplyConfiguration(new CityConfiguration())
        .ApplyConfiguration(new CountryConfiguration())
        .ApplyConfiguration(new PropertyConfiguration());
}
```