Option	Description
`--model|-m`	Model class to use
`--dataContext|-dc`	`DbContext` class to use
`--referenceScriptLibraries|-scripts`	Switch to specify whether to reference script libraries in the generated views
`--layout|-l`	Custom layout page to use
`--useDefaultLayout|-udl`	Switch to specify that the default layout should be used for the views
`--force|-f`	Overwrites existing files
`--relativeFolderPath|-outDir`	Specifies the relative output folder path from project where the file needs to be generated; if not specified, the file will be generated in the project folder
`--namespaceName|-namespace`	Specifies the name of the namespace to use for the generated `PageModel`
`--partialView|-partial`	Generates a partial view; other layout options (`-l` and `-udl`) are ignored if this is specified
`--noPageModel|-npm`	Switch to prevent generating a `PageModel` class for an empty template
`--useSqlite|-sqlite`	Flag to specify if `DbContext` should use SQLite instead of SQL Server

You can scaffold individual pages based on the existing templates by specifying a name for the Razor page as well as the name of the template to use, which is one of the following options: `Empty`, `Create`, `Edit`, `Delete`, `Details`, or `List`. Or you can omit the name and template; in which case, the generator will scaffold all except the empty template.

You want to scaffold all CRUD pages for the `Property` class, and you want to use the `CityBreaksContext` as the data context. You also want the generated files to be placed in the Pages\PropertyManager folder, and you want them to use the default layout page for that folder. You won't