public property that enables you to use the value in both handler methods, and you will ensure it can be bound to when the request uses the `GET` method.

Listing 8.27 Replacing binding to entity with binding to properties

```
public SelectList Cities { get; set; }
[BindProperty(SupportsGet = true)]
public int Id { get; set; }
[BindProperty, Display(Name = "City")]
public int CityId { get; set; }
[BindProperty, Required]
public string Name { get; set; }
[BindProperty, Required]
public string Address { get; set; }
[BindProperty, Display(Name = "Maximum Number Of Guests")]
public int MaxNumberOfGuests { get; set; }
[BindProperty, Display(Name = "Daily Rate")]
public decimal DayRate { get; set; }
[BindProperty, Display(Name = "Smoking?")]
public bool SmokingPermitted { get; set; }
[BindProperty, Display(Name = "Available From")]
public DateTime AvailableFrom { get; set; }
```

You need to populate the `Cities SelectList` property in the `OnGetAsync` handler and again in the `OnPostAsync` handler if there are `ModelState` errors. You have already established a pattern for this that reduces duplication. In listing 8.28, you add a private method that returns a `SelectList` that uses asynchronous code to the end of the `PageModel` class.

Listing 8.28 The reusable private method for populating `SelectList` objects

```
private async Task<SelectList> GetCityOptions()
{
    var cities = await _cityService.GetAllAsync();
    return new SelectList(cities, nameof(City.Id), nameof(City.Name));
}
```