You will have lots of squiggly red lines indicating compiler errors now. You tackle those in the `OnGetAsync` method first by replacing the entire method block with the following code, which uses the service to obtain the `Property` instance to be edited and assigns its values to the public `PageModel` properties.

Listing 8.29 The amended `OnGetAsync` method

```
public async Task<IActionResult> OnGetAsync()
{
    var property = await _propertyService.FindAsync(Id);

    if (property == null)
    {
        return NotFound();
    }
    Address = property.Address;
    AvailableFrom = property.AvailableFrom;
    CityId = property.CityId;
    DayRate = property.DayRate;
    MaxNumberOfGuests = property.MaxNumberOfGuests;
    Name = property.Name;
    SmokingPermitted = property.SmokingPermitted;

    Cities = await GetCityOptions();
    return Page();
}
```

The code that maps values from the entity you retrieved from the database to `PageModel` properties is manageable for your relatively simple entity. You can imagine this type of code will be laborious to write and maintain for entities with more properties. Tools that can help reduce this code significantly—to a single line, in many cases—are available, such as the popular AutoMapper (https://automapper.org/), which is my preferred option. You won't be using such a tool in this book, but I recommend exploring this massive time saver for your own applications.

That just leaves the `OnPostAsync` method to tidy before moving the Razor part of the page. The scaffolded code catches a