We will explore authorization in more detail in the next chapter, but for the time being, authorization middleware needs to have information about the current user (produced by the authentication middleware) and the current endpoint (selected by routing middleware) to know whether to short-circuit the pipeline if the current user doesn't have authority to access the selected endpoint or allow the request to flow to endpoint middleware, so the selected endpoint can be executed. Next, you will create a new Razor page in the Pages folder, named Login. You will add a very simple form that captures just the name, using the code in the following listing.

Listing 9.3 The simple login form

```
@page
@model CityBreaks.Pages.LoginModel
@{
}
<div class="col-4">
    <form method="post">
        <div class="mb-3">
            <label class="form-label" asp-for="UserName"></label>
            <input class="form-control" asp-for="UserName" />
        </div>
        <div class="mb-3">
            <button class="btn btn-outline-primary">Sign in</button>
        </div>
    </form>
</div>
```

Now, turning to the `PageModel`, you will need to add the using directives shown in the next listing.

Listing 9.4 The using directives required by the LoginModel class

```
using Microsoft.AspNetCore.Authentication;
using Microsoft.AspNetCore.Authentication.Cookies;
using System.Security.Claims;
using System.ComponentModel.DataAnnotations;
```

The `PageModel` class itself (`LoginModel`) features a bound property for the `UserName`, and an asynchronous `OnPost` handler, where you sign the user in with the username supplied.