Listing 9.5 The `LoginModel` class

```
public class LoginModel : PageModel
{
    [BindProperty, Display(Name="User name")]                    ❶
    public string UserName { get; set; }                         ❶

    public async Task OnPostAsync()
    {
        var claims = new List<Claim>                             ❷
        {                                                        ❷
            new Claim(ClaimTypes.Name, UserName)                 ❷
        };                                                       ❷
        var identity = new ClaimsIdentity(claims,
        ➥ CookieAuthenticationDefaults.AuthenticationScheme);   ❸
        var principal = new ClaimsPrincipal(identity);           ❹
        await HttpContext.SignInAsync(principal);                ❺
    }
}
```

❶ The UserName property is assigned as a binding target.

❷ Assign the username to a claim.

❸ Create an identity based on the claim.

❹ Use the identity to create a ClaimsPrincipal.

❺ Sign the principal in.

Concentrating on the `OnPostAsync` handler in listing 9.5, you first create a claim. *Claims* are pieces of information about the user stored consistently: the name of the claim and, optionally, a value. This is the basis of *claims-based authentication*, which is what ASP.NET Core uses. For example, I claim to have the name Mike Brind. I also claim to be an author (albeit an accidental one). And I claim to be able to drive a car ... better than Lewis Hamilton. OK, so some of my claims might not stand up to scrutiny, but we will look at that a bit later.

You will use the claim to create an *identity*. The identity is a specific type that supports claims: a `ClaimsIdentity`. As you may well deduce from the fact that the claim used to construct this identity is part of a collection, an identity can support multiple claims. This identity is used to construct a `ClaimsPrincipal`, representing the user logging in. The `ClaimsPrincipal` is capable of supporting multiple identities, which also