application. You will call your user class `CityBreaksUser`. Add the following class to the Models folder.

Listing 9.9 The `CityBreaksUser` class

```
using Microsoft.AspNetCore.Identity;

namespace CityBreaks.Models
{
    public class CityBreaksUser : IdentityUser      ❶
    {
    }
}
```

❶ Your user class derives from IdentityUser.

At this stage, we will only work with the default properties of the `IdentityUser`. We will look at customizing this class a bit later.

9.2.2 Configuring the DbContext

The next stage involves adapting the existing `CityBreaksContext` to work with Identity. Two amendments are required for this (listing 9.10). The first is to derive your context class from `IdentityDbContext<TUser>`, instead of `DbContext`, where `TUser` represents the user class you just created. The `IdentityDbContext` includes some `DbSet` properties, representing database tables Identity uses to store various aspects of user data. You also need to include a `using` directive for `Microsoft.AspNetCore.Identity.EntityFrameworkCore`.

Listing 9.10 Adapting the `DbContext` to work with Identity

```
using CityBreaks.Data.Configuration;
using CityBreaks.Models;
using Microsoft.AspNetCore.Identity.EntityFrameworkCore;    ❶
using Microsoft.EntityFrameworkCore;

namespace CityBreaks.Data
```