```
    await _userStore.SetUserNameAsync(user, Input.Email,
    ➥ CancellationToken.None);
    await _emailStore.SetEmailAsync(user, Input.Email,
    ➥ CancellationToken.None);
    var result = await _userManager.CreateAsync(user, Input.Password);
```

❶ Here you assign the bound values to the custom properties you added to your implementation of the IdentityUser.

You make two modifications to the Razor page—the first to comment out or remove the same block of code about external logins you dealt with in the Login page and the second to add the following form fields at the beginning of the form, just below the validation summary tag helper.

Listing 9.20 The forms fields for the additional `IdentityUser` properties

```
<div class="form-floating">
    <input asp-for="Input.FirstName" class="form-control" />
    <label asp-for="Input.FirstName"></label>
    <span asp-validation-for="Input.FirstName" class="text-danger"></span>
</div>
<div class="form-floating">
    <input asp-for="Input.LastName" class="form-control" />
    <label asp-for="Input.LastName"></label>
    <span asp-validation-for="Input.LastName" class="text-danger"></span>
</div>
<div class="form-floating">
    <textarea asp-for="Input.Address" class="form-control"></textarea>
    <label asp-for="Input.Address"></label>
    <span asp-validation-for="Input.Address" class="text-danger"></span>
</div>
```

Now you can run the application and click the Register as a New User link on the Login page, which should take you to the revised form shown in figure 9.14. Complete it (with a different email address), and submit. You should find yourself logged in, and you should also see that the additional fields were populated in the `AspNetUsers` table.