9.3.4 Enabling email confirmation

Identity supports some scenarios that utilize email. For example, you can require a user to confirm they have control over the email address they use to register with by sending them an email containing a link they must click to validate their registration. Password reset features also rely on email. The Identity UI incorporates an email service represented by the `IEmailSender` interface. It has one method, `SendEmailAsync`, which in the default implementation does nothing at all.

Listing 9.21 The default `EmailSender` service

```
internal class EmailSender : IEmailSender
{
    public Task SendEmailAsync(string email, string subject, string htmlMessage)
    {
        return Task.CompletedTask;
    }
}
```

You don't have to use the `IEmailSender` interface. You can use whatever you like, but in this example, you will provide your own implementation that generates an email using an open source email management library called MailKit (http://mng.bz/69GA). Countless examples all over the internet (and on my sites) demonstrate how to send email from ASP.NET applications by using classes in the `System.Net.Mail` class, but this approach is now obsolete. Instead, Microsoft recommends that you use more modern libraries, with MailKit specifically mentioned as an example in their documentation. So the first thing you need to do is to install the package:

```
[CLI]
dotnet add package MailKit
[Package Manager Console]
install-package MailKit
```

Next add a new folder to the root of the project named TempMail. You will emulate the `SpecifiedPickupDirectory` delivery method provided