by the obsolete `System .Net.Mail` class. This enables you to specify a location on disk in which email messages generated by the mail library are placed. This is useful for testing and debugging because it means you don't have to rely on network availability. MailKit doesn't support `SpecifiedPickupDirectory` out of the box, so you will provide your own implementation based on code from the project's FAQ (http://mng.bz/YK8z).

Add a new class file to the Services folder, and name it EmailService.cs. Replace any existing content with the code in the following listing.

Listing 9.22 The `EmailService` class

```
using MailKit.Net.Smtp;
using Microsoft.AspNetCore.Identity.UI.Services;
using MimeKit;
using MimeKit.IO;

namespace CityBreaks.Services
{
    public class EmailService : IEmailSender                                    ❶
    {
        private readonly IHostEnvironment _environment;                         ❷
        public EmailService(IHostEnvironment environment)                       ❷
        {                                                                       ❷
            _environment = environment;                                         ❷
        }                                                                       ❷
        public async Task SendEmailAsync(string email, string subject,          ❷
        ➥ string htmlMessage)
        {
            var pickupDirectory = Path.Combine(_environment.ContentRootPath,    ❸
            ➥ "TempMail");                                                     ❸
            var message = new MimeMessage();                                    ❹
            message.From.Add(MailboxAddress.Parse(                              ❹
            ➥ "test@test.com"));                                               ❹
            message.To.Add(MailboxAddress.Parse(email));                        ❹
            message.Subject = subject;                                          ❹

            message.Body = new TextPart("html")                                 ❹
            {                                                                   ❹
                Text = htmlMessage                                              ❹
            };                                                                  ❹

            Await SaveToPickupDirectory(message, pickupDirectory);              ❺
```