intend to implement. For example, several pages at the identity/account/manage endpoint allow users to change their personal data, get a copy of it, delete it, manage 2FA, and so on. We will look at ways to manage these in the next section.

Before we move on, there is one thing you should bear in mind about how this feature works. The link in the generated email includes a validation token within the query string. The token is encoded using Base64 URL encoding (http://mng.bz/09YJ). The resulting value includes mixed-case characters. If you have `LowercaseQueryStrings` set to `true` within your routing options, the encoded value will be altered to all lowercase, breaching the token's integrity. In this scenario, the token will always fail validation.

9.3.5 Disabling UI features

When you include the UI package, you opt in to all of it. There will, undoubtedly, be parts you don't want to implement. You have a choice of how you want to disable these features. You can use authorization to prevent unauthorized access, while maintaining the functionality of the pages, which we will look at in the next chapter.

It is, of course, possible to remove links to any pages you don't want users to access. However, that is not a foolproof solution. Other savvy developers may well recognize the Identity UI URL scheme when they visit or use your application and could be tempted to poke around. Instead, you can scaffold the pages you don't want to implement and alter their code to disable them.

In this example, you will scaffold the LoginWith2Fa page and disable it. If you are using Visual Studio, use the Add... New Scaffolded Item option to generate Account\ LoginWith2fa. Or, using the CLI, execute the following command:

```
dotnet aspnet-codegenerator identity -dc CityBreaks.Data.CityBreaksContext
➥ -sqlite -fi Account.LoginWith2fa
```