Figure 10.1 Middleware authorization order depends on knowing who the user is and where they are trying to go. If the user is not authorized, the pipeline is short-circuited. Otherwise, the request flows through to endpoint middleware, and the page is executed.

Given that you do not want to execute pages the current user is not authorized to access, the only logical position within the pipeline to place `UseAuthorization` is *after* `UseRouting` and `UseAuthentication` and *before* `MapRazorPages`. For that reason, authorization middleware must be placed after the authentication middleware and before the call to `MapRazorPages` (listing 10.1).

Listing 10.1 The position of `app.UseAuthorization` is critical

```
app.UseRouting();                ❶
app.UseAuthentication();         ❶
app.UseAuthorization();
app.MapRazorPages();             ❷
```

❶ Routing and authentication middleware must be placed *before* authorization middleware.

❷ Endpoint middleware must be placed *after* authorization middleware.

10.1.1 Applying simple authorization

You will use the `AuthorizeAttribute` to apply authorization to endpoints. The attribute has some properties, among which are `Roles` and `Policy`, which you will explore in more detail as you work through the chapter. At its most basic, when you apply the attribute to an endpoint, it prevents access to that endpoint to anonymous users. Users must authenticate to become authorized to proceed.

There are a number of ways you can apply the attribute to an endpoint. The simplest way to add it to the `PageModel` class.