a class named `PropertyOperations`. This class is placed in the AuthorizationRequirements folder.

Listing 10.25 Implementing `OperationAuthorizationRequirements`

```
using Microsoft.AspNetCore.Authorization.Infrastructure;                ❶

namespace CityBreaks.AuthorizationRequirements
{
    public static class PropertyOperations                              ❷
    {
        public static OperationAuthorizationRequirement Create =
            new () { Name = nameof(Create) };                            ❸
        public static OperationAuthorizationRequirement Read =
            new () { Name = nameof(Read) };
        public static OperationAuthorizationRequirement Edit =
            new () { Name = nameof(Edit) };
        public static OperationAuthorizationRequirement Delete =
            new () { Name = nameof(Delete) };
    }
}
```

❶ The OperationAuthorizationRequirement helper class is in the Microsoft.AspNetCore.Authorization.Infrastructure namespace.

❷ PropertyOperations is a wrapper class for multiple authorization requirements relating to operations on the Property type.

❸ An instance of OperationAuthorizationRequirement is instantiated with its Name set to Create. Others are instantiated with their names set to other CRUD operations.

Now that you have your requirement classes, you can create handlers. In fact, because the requirement type is the same for all operations (a key benefit to using the `OperationAuthorizationRequirement` class), you only need to create one handler—one that is based on `AuthorizationHandler<TRequirement, TResource>`, where `TResource` represents the type of the resource being authorized.

The handler class is named `PropertyAuthorizationhandler` and is placed in the AuthorizationHandlers folder. For brevity, it only contains checks for two of the operations: `Edit` and `Delete`. Since the