Many other client-side libraries took dependencies on jQuery, including the leading UI framework library, Bootstrap, which is bundled into the default ASP.NET Core web application templates. The latest version of Bootstrap (version 5) included in the new templates from .NET 6 onwards dropped its dependency on jQuery. These days, most browsers adhere to standards much more closely than they used to. Many of them share the same underlying technology. The problem jQuery was designed to solve has largely disappeared.

Despite that, jQuery is still included in the default Razor Pages applications template to provide support for client-side validation. In the longer term, this may well change because there is an open issue on GitHub that discusses the potential replacement of client-side validation so that it no longer depends on jQuery (https://github.com/dotnet/aspnetcore/issues/8573). Nevertheless, jQuery is still widely used, so in this chapter, we will look at implementing client-side solutions using both jQuery and plain JavaScript.

Other client-side libraries exist. Probably the most widely used among them are React and Angular. Angular is more accurately referred to as an application framework, but both are primarily used for building single-page applications (SPAs) for which workflow logic executes in the browser rather than on the server. They *can* be used as part of a Razor Pages application, but they are overkill if all you want to do is add isolated instances of client-side functionality.

11.2 Calling page handlers from JavaScript

This section focuses on calling named page handler methods from client-side code. We will cover how to use a partial page to return a snippet of HTML you can use to update a section of a page. Then we will explore how to post