```
<div class="modal fade" id="property-modal">
  <div class="modal-dialog">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title">Property Details</h5>
        <button type="button" class="btn-close"
        ➥ data-bs-dismiss="modal" aria-label="Close"></button>
      </div>
      <div class="modal-body">

      </div>
      <div class="modal-footer">
        <button type="button" class="btn btn-secondary"
        ➥ data-bs-dismiss="modal">Close</button>
      </div>
    </div>
  </div>
</div>
```

This code is more or less lifted straight out of the Bootstrap 5 documentation for modals. It is a standard modal with no content in its body. You have changed the title to be more relevant to your application and added an `id` attribute, so you can identify the modal from client code. You have also added the `fade` class to the modal, so it animates when appearing and disappearing.

Now you need some content for your modal. This will be placed in another partial named _PropertyDetailsPartial.cshtml, which is also placed in the Pages\Shared folder. Its content is simple. You pass a `Property` in as the model for the Razor file and render details of the property as follows.

Listing 11.2 The partial containing the property details that will be loaded

```
@model Property
<h3>@Model.Name</h3>
<address>
    @Model.Address
</address>
<p>Availability: @(Model.AvailableFrom < DateTime.Now ?
➥ "Immediate" : Model.AvailableFrom.ToShortDateString())</p>
```