`role="button"` assigned to it, so the cursor becomes a pointer when the user hovers over the heading. You need to modify the heading to add some `data` attributes. One will help you identify the specific property, and others are used to trigger the modal. I've broken the resulting declaration of the `h5` element over several lines in the following listing, so it is easier to annotate the code.

Listing 11.5 The amended `h5` element designed to trigger a modal

```
<h5 role="button"
data-id="@property.Id"                    ❶
data-bs-toggle="modal"                    ❷
data-bs-target="#property-modal"          ❸
>@property.Name</h5>
```

❶ The data-id attribute has the property Id assigned to it. You will retrieve this value and pass it to the named page handler you just added.

❷ This Bootstrap custom attribute makes the element a trigger for a modal.

❸ This attribute takes the id of the target modal.

Finally, include the modal partial in the page (listing 11.6), and use the `scripts` section to add a block of JavaScript. The client-side code uses jQuery to add a click event handler to all `h5` elements. Within the click handler, the `id` of the specified property is retrieved from the `data-id` attribute. A URL is constructed, with query string parameters representing the name of the page handler method and its `id` parameter. This is used in the jQuery load method that uses the `GET` method to make an HTTP request and then loads the response into the specified element.

Listing 11.6 Adding a partial and the script block to the page

```
<partial name="_PropertyModalPartial" />                    ❶
@section scripts{
<script>
$(function(){
```