```
    $('h5').on('click', function() {                                    ❷
        const id = $(this).data('id');                                  ❸
        $('.modal-body').load(`?handler=propertydetails&id=${id}`);     ❹
    });
});
</script>
}
```

❶ Use a partial tag helper to include the modal partial.

❷ Add a click event handler to all h5 elements.

❸ Within the handler, retrieve the Id of the selected property from the data-id attribute.

❹ The jQuery load method uses the GET method to call the specified URL and inserts the response into the element specified in the selector. In this case, that's the modal body.

Run the application, click a city on the home page, and then click the property's name in the resulting list. The details should appear in the modal.

Removing the reliance on jQuery, you can use the Fetch API instead, which is supported by all modern browsers. The only change you need to make is to the `scripts` section.

Listing 11.7 Calling a named handler with the Fetch API

```
@section scripts{
<script>
document.querySelectorAll('h5').forEach(el => {                         ❶
    el.addEventListener('click', (event) => {                           ❶
        const id = event.target.dataset.id;                             ❷
        fetch(`?handler=propertydetails&id=${id}`)                      ❸
        .then((response) => {
            return response.text();                                     ❹
        })
        .then((result) => {
            document.querySelector('.modal-body').innerHTML = result;   ❺
        });
    });
});
</script>
}
```

❶ Add a click event handler to all h5 elements.