```
$('.btn-success').on('click', function(){
    const token = $('[name="__RequestVerificationToken"]').val();    ❶
    const data = {
            startdate: $('#StartDate').val(),
            enddate: $('#EndDate').val(),
            numberofguests: $('#NumberOfGuests').val(),
            property:{
                dayrate: $('#Property_DayRate').val()
            }
        }
    $.ajax({
        url: '?handler=booking',
        method: "post",
        contentType: "application/json",                             ❷
        headers: {
            "RequestVerificationToken" : token                       ❸
        },
        data: JSON.stringify(data)                                   ❹
    })
    .done(function(response){
        alert(`Your stay will cost ${response.totalCost}`);
    });
});
```

❶ Get the token value.

❷ Set the content type via the contentType option.

❸ Pass the token in a header.

❹ Use the JSON.stringify method to serialize the JavaScript object to JSON format.

The key points to working with page handlers and JSON are as follows:

- Remember to apply the `FromBody` attribute to handler parameters.
- Set the content type of the request to `application/JSON`.
- Pass the request verification token in the request header.
- Use the Network tab in the browser developer tools to diagnose issues.

In my opinion, using a page handler method to process and return JSON is acceptable in moderation. Remember that every time a page handler is executed, an instance of the `PageModel` is instantiated, and all of its dependencies are resolved. If you find you are injecting additional